

CladCure



easy-trim[®] WaterProofing

Description

CladCure is a liquid applied waterproofing system designed for use on external metal cladding. It is formulated using synthetic resins and fast drying solvents ensuring the optimum bond to difficult substrates. CladCure is available in a wide range of standard colours, offering limitless design opportunities for refurbishment projects. A 10 year guarantee is offered by Easy-Trim Roofing and Construction Products.

Benefits

- Saves the cost of completely re-cladding
- Flexible, cold applied, rapid & simple application
- Low temperature application means CladCure is suitable for year round use
- Overcoat in about 1 hour in ventilated conditions
- No hot works insurance required
- Tins can be opened and re-sealed with no surface skinning inside the can
- Resistant to industrial and environmental pollution
- Spray, roller or brush application options
- RAL colour matching available - subject to minimum order quantities

Application

Substrate Preparation: Jet wash existing surfaces using a 3000psi turbo jet. All moss, lichen or fungal growth should be removed. Clean using a mild soap solution. All substrates should be free of any standing water. Metal surfaces should be free of loose rust, mill scale and flaking coatings, and cleaned and degreased with surface cleaner. All damaged sheets should be repaired with our CladCure system or same profile repairs can be enacted if holes are present. These repairs should be riveted into place and then repaired as below.

Priming: No priming is usually required

Small Repairs: Clean damaged sections of the sheets and apply CladCure at a coverage rate of 0.6L/m², allowing a 100mm border around the edges of the section. Into this, bed the Easy-Trim GFR 225 matting (150mm roll width available) and pull through the CladCure with a roller on the surface. Add a further 0.4L/m² whilst still wet to fully encapsulate the matting.

Application: Apply CladCure using airless spray or roller. The product must not be applied in wet or freezing conditions or if these conditions are likely to occur before the membrane has dried. The product is applied in a single coat. Normal drying time is 2 to 4 hours. Clean tools using tool cleaner.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



CladCure

Application - Continued

Coverage Rates: 0.6L/m²

Temperature: Drying times can vary with ambient air and deck temperature. CladCure must not be applied in freezing conditions or if these conditions are likely to occur before the membrane has dried. To apply at temperatures between 0°C to 40°C.

Storage: Store in dry, cool conditions, preferably at temperatures between 10°C and 20°C.

Site Testing: The above coverage rates are for guidance only. Site application tests are recommended to confirm actual coverage rates.

Durability

CladCure protects metal from further corrosion, and cladded surfaces from further infra red and ultra violet damage, thermal movement and heat build up whilst resisting industrial and environmental pollution when subjected to normal service conditions. CladCure should be inspected annually as part of a regular maintenance programme.

Components

CladCure: 5L & 15L Units

Easy-Trim GFR 225: 150mm x 20mtr & 250mm x 20mtr

Typical Physical Performance Data

Colour	Dark Grey
Pack Sizes	5L & 15L
Shelf Life	12 Months
Application Surface Temperature Limits	0 to 40°C
Curing Time	1 to 2 hours (in ventilated conditions)
One coat application	

For further information please refer to: MSDS (Material Safety Data Sheet). For specific advice on chemical resistance and further installation guidance please contact Easy Trim technical department.

Disclaimer

The information relates only to this specified material and may not be valid for such materials used in combinations with other materials and processes. This information is, to the best of the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of the information on the material for their own particular use.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

